## AMENDMENTS TO THE CLAIMS

Please amend claims as follows:

1-123. (Cancelled).

124. (Currently amended) A method for fabricating an orthopedic implant prosthesis bearing, comprising the steps of:

pre-heating an ultrahigh molecular weight polyethylene (UHMWPE) preform at a temperature greater than ambient room temperature and less than the decomposition temperature of the UHMWPE for a period of time greater than 30 minutes;

irradiating the UHMWPE preform, thereby crosslinking the UHMWPE preform; and

quenching reducing residual free radicals in the crosslinked UHMWPE preform by heating the irradiated UHMWPE.

- 125. (Currently amended) The method of claim 124, further comprising the steps of: cooling the preform after the quenching heating step to a temperature below the melting temperature of the <u>irradiated</u> UHMWPE; and forming the preform into a prosthetic bearing.
- 126. (Currently amended) A method for fabricating an orthopaedic implant prosthesis bearing comprising the steps of:

pre-heating an ultrahigh molecular weight polyethylene (UHMWPE) preform; irradiating the UHMWPE preform, thereby crosslinking the UHMWPE preform; quenching reducing residual free radicals in the crosslinked UHMWPE preform subsequent to the irradiating step by heating the irradiated UHMWPE and forming the UHMWPE preform into a prosthetic bearing.

127. (Currently amended) A method for fabricating an orthopaedic implant prosthesis bearing comprising the steps of:

pre-heating an ultrahigh molecular weight polyethylene (UHMWPE) preform;

irradiating the UHMWPE preform, thereby crosslinking the UHMWPE preform;

quenching reducing residual free radicals in the crosslinked UHMWPE preform subsequent to the irradiating step by heating the irradiated UHMWPE; and forming the UHMWPE preform into a prosthetic bearing.

128. (Withdrawn) A method for fabricating an orthopedic implant prosthesis bearing, comprising the steps of:

melting a polyethylene preform for a period of time greater than about 30 minutes:

irradiating the polyethylene preform to crosslink the polyethylene preform; and quenching residual free radicals in the polyethylene preform.

129. (Withdrawn) The method of claim 128, further comprising the steps of:

cooling the preform after the quenching step to a temperature below the melting temperature of the polyethylene; and

forming the preform into a prosthetic bearing.

130. (Withdrawn) A method for fabricating an orthopaedic implant prosthesis bearing comprising the steps of:

melting an ultrahigh molecular weight polyethylene preform;

irradiating the ultrahigh molecular weight polyethylene preform to crosslink the ultrahigh molecular weight polyethylene preform;

quenching residual free radicals in the ultrahigh molecular weight polyethylene preform subsequent to the irradiating step; and

forming the ultrahigh molecular weight polyethylene preform into a prosthetic bearing.

131. (Withdrawn) A method for fabricating an orthopaedic implant prosthesis bearing comprising the steps of:

melting a polyethylene preform;

irradiating the polyethylene preform to crosslink the polyethylene preform;

quenching residual free radicals in the polyethylene preform after an irradiation; and

forming the polyethylene preform into a prosthetic bearing.

- 132. (Withdrawn) The method according to claim 128, wherein the polyethylene is ultrahigh molecular weight polyethylene.
- 133. (Withdrawn) A method for fabricating an orthopaedic implant prosthesis bearing comprising the steps of:

irradiating a polyethylene preform that has been melted, thereby crosslinking the polyethylene

quenching residual free radicals in the polyethylene preform after an irradiation; and

forming the polyethylene preform into a prosthetic bearing.

- 134. (Withdrawn) The method according to claim 133, wherein the polyethylene is ultrahigh molecular weight polyethylene.
- 135. (Currently amended) The method of claim 124, wherein the quenching step of reducing residual free radicals is carried out by heating the irradiated UHMWPE preform to a temperature above ambient room temperature.
- 136. (Currently amended) The method of claim 126, wherein the quenching step of reducing residual free radicals is carried out by heating the irradiated UHMWPE preform to a temperature above ambient room temperature.
- 137. (Currently amended) The method of claim 127, wherein the quenching step of reducing residual free radicals is carried out by heating the irradiated UHMWPE preform to a temperature above ambient room temperature.

- 138. (Previously presented) The method of claim 124, wherein the UHMWPE preform is irradiated at a dose of about 4 Mrads to about 30 Mrads.
- 139. (Previously presented) The method of claim 126, wherein the UHMWPE preform is irradiated at a dose of about 4 Mrads to about 30 Mrads.
- 140. (Previously presented) The method of claim 127, wherein the UHMWPE preform is irradiated at a dose of about 4 Mrads to about 30 Mrads.